



Home Innovation
NGBS GREEN CERTIFIED™

THIS SIGNIFIES THE FOLLOWING CONSTRUCTION PRODUCTS

WOLMANIZED® OUTDOOR® WOOD, WOLMANIZED ERAWOOD®
LUMBER, AND TANALISED® MICRONISED COPPER AZOLE (MCA)
TIMBER

MANUFACTURED BY

ARXADA

ARE CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO THE ICC 700
NATIONAL GREEN BUILDING STANDARD, AS DETAILED BELOW.


Michael Luzier – President & CEO

04-26-2010
Approval Date

05-31-2026
Expiration Date

CERTIFICATE # 131

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certificate #NGBSGCP-000131

Product: Wolmanized® Outdoor® Wood, Wolmanized EraWood® Lumber, and Tanalised® Micronised Copper Azole (MCA) Timber

Manufacturer: Arxada

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2020 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONAL OF USE TO AWARD POINTS
602.1.6	Termite-resistant materials are used for the foundation, all structural walls, floors, concealed roof spaces not accessible for inspection, exterior decks, and exterior claddings within the first 2 ft above the top of the foundation. 2 points available.	2-6	To earn 2 points, product is used in conjunction with other termite-resistant materials for the first 2 ft of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in conjunction with other termite-resistant materials for the first 3 ft in moderate to heavy termite zones, and 6 points are awarded for use with other termite-resistant materials for all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.