



**Home Innovation**  
NGBS GREEN CERTIFIED™


THIS SIGNIFIES THE FOLLOWING CONSTRUCTION PRODUCTS

**PANGO® WRAP TERMITE/VAPOR BARRIER**

MANUFACTURED BY

**STEGO INDUSTRIES, LLC**

ARE CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO THE ICC 700  
NATIONAL GREEN BUILDING STANDARD, AS DETAILED BELOW.

  
Michael Luzier – President & CEO

03-08-2016  
Approval Date

04-30-2026  
Expiration Date

**CERTIFICATE # 267**

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certificate #NGBSGCP-000267

Product: Pango® Wrap Termite/Vapor Barrier

Manufacturer: Stego Industries, LLC

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

<b>2020 NATIONAL GREEN BUILDING STANDARD</b>			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONAL OF USE TO AWARD POINTS
602.1.1.1	A capillary break and vapor retarder are installed at concrete slabs. Mandatory.	Mandatory	Products are installed in accordance with IRC Section R506.2.2 and R506.2.3 or IBC Sections 1910 and 1805.4.1. This product qualifies as a vapor retarder and must be installed in conjunction with a capillary break to earn points.
602.1.5(1-2)	A termite barrier is installed.	4	To earn points, products must be installed in geographic areas with termite potential, as determined in accordance with Figure 6(3).
602.1.4.1(1)	Min 6-mil vapor retarder is installed on the crawlspace floor that extends at least 6" up the wall and is attached and sealed to the wall. 6 points available.	6	Product is installed on the crawlspace floor of unconditioned vented crawl as directed.
902.3.1.1	There is a continuous gas-permeable base course under each soil-gas retarder that is separated by foundation walls or footings. The soil-gas retarder is a continuous 6-mil (0.15 mm) polyethylene or equivalent. Compliance option for 902.3(1) and 902.3(2).	Mandatory	Items 902.3.1.2 through 902.3.1.7 are also met. Mandatory for buildings in Zone 1. For Zone 2 or 3 buildings, 6 points if a passive radon system is installed OR 12 points if an active radon system is installed.

<b>2020 NATIONAL GREEN BUILDING STANDARD</b>			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONAL OF USE TO AWARD POINTS
602.1.4.2(1)	When crawlspace is built as conditioned space, crawlspace is sealed using a concrete slab over 6-mil polyethylene sheeting or other Class I vapor retarder. 8 points available.	8	Product is installed on the crawlspace walls of unconditioned vented crawl as directed.
602.1.4.2(2)	When crawlspace is built as conditioned area, crawlspace is sealed using 6-mil polyethylene sheeting, or other Class I vapor retarder. Mandatory.	Mandatory	Product is installed in accordance with Section 408.3 or Section 506 of the IRC.